

~~SECRET~~  
HANDLE VIA BYEMAN  
CONTROL SYSTEM

AA 8380/w

1. RELAXATION OF THE ATTITUDE ERROR TO 10 ARC SECONDS IN EACH COMPONENT WILL SATISFY CURRENT KWETHER REQUIREMENTS.

WORKING COPY

BT

NNNN

~~SECRET~~  
HANDLE VIA BYEMAN  
CONTROL SYSTEM

| DISPOSITION |   |  |
|-------------|---|--|
| SERIAL      | A |  |
| 54100       |   |  |
| 00          |   |  |
| 50-1        |   |  |
| 50-2        |   |  |
| 50-3        |   |  |
| 50-4        |   |  |
| 50-5        |   |  |
| 50-6        |   |  |
| 50-7        |   |  |
| 50-8        |   |  |
| 50-9        |   |  |
| 50-10       |   |  |
| 50-11       |   |  |
| 50-12       |   |  |
| 50-13       |   |  |
| 50-14       |   |  |
| 50-15       |   |  |
| 50-16       |   |  |
| 50-17       |   |  |
| 50-18       |   |  |
| 50-19       |   |  |
| 50-20       |   |  |
| 50-21       |   |  |
| 50-22       |   |  |
| 50-23       |   |  |
| 50-24       |   |  |
| 50-25       |   |  |
| 50-26       |   |  |
| 50-27       |   |  |
| 50-28       |   |  |
| 50-29       |   |  |
| 50-30       |   |  |
| 50-31       |   |  |
| 50-32       |   |  |
| 50-33       |   |  |
| 50-34       |   |  |
| 50-35       |   |  |
| 50-36       |   |  |
| 50-37       |   |  |
| 50-38       |   |  |
| 50-39       |   |  |
| 50-40       |   |  |
| 50-41       |   |  |
| 50-42       |   |  |
| 50-43       |   |  |
| 50-44       |   |  |
| 50-45       |   |  |
| 50-46       |   |  |
| 50-47       |   |  |
| 50-48       |   |  |
| 50-49       |   |  |
| 50-50       |   |  |
| 50-51       |   |  |
| 50-52       |   |  |
| 50-53       |   |  |
| 50-54       |   |  |
| 50-55       |   |  |
| 50-56       |   |  |
| 50-57       |   |  |
| 50-58       |   |  |
| 50-59       |   |  |
| 50-60       |   |  |
| 50-61       |   |  |
| 50-62       |   |  |
| 50-63       |   |  |
| 50-64       |   |  |
| 50-65       |   |  |
| 50-66       |   |  |
| 50-67       |   |  |
| 50-68       |   |  |
| 50-69       |   |  |
| 50-70       |   |  |
| 50-71       |   |  |
| 50-72       |   |  |
| 50-73       |   |  |
| 50-74       |   |  |
| 50-75       |   |  |
| 50-76       |   |  |
| 50-77       |   |  |
| 50-78       |   |  |
| 50-79       |   |  |
| 50-80       |   |  |
| 50-81       |   |  |
| 50-82       |   |  |
| 50-83       |   |  |
| 50-84       |   |  |
| 50-85       |   |  |
| 50-86       |   |  |
| 50-87       |   |  |
| 50-88       |   |  |
| 50-89       |   |  |
| 50-90       |   |  |
| 50-91       |   |  |
| 50-92       |   |  |
| 50-93       |   |  |
| 50-94       |   |  |
| 50-95       |   |  |
| 50-96       |   |  |
| 50-97       |   |  |
| 50-98       |   |  |
| 50-99       |   |  |
| 50-100      |   |  |