NRO APPROVED FOR RELEASE **DECLASSIFIED BY: C/IART DECLASSIFIED ON: 9 JULY 2012**

14 December 1962



MEMORANDUM FOR MR. McCONE

In accordance with your request through Mr. Sceville this memorandum is a summary of the Satellite Reconnissance Program and its current status. A current schodule is strached.

The CORONA-MURAL 24" focal length steres mearch system. is operational. Thirteen of sixteen flights have returned material for exploitation with average resolution of ten to thirteen feet. A small percentage of the material has measured resolution down to neven feet and a portion of the material has resolution ranging up to twenty feet. The system also includes a l. 5 inch focal length framing camera and 25 mm stellar camera unit to enhance the use of the panoramic recommissance photography.

In May of 1963 the CORONA-J configuration should be available for test. The CORONA-J is identical with the CORONA-M system except that the vehicle is modified to have two complete recovery systems. The operational plan for this system is to operate for four days and then recover the first capsule. The vehicle may then be placed in an inactive mode and reactivated at any time up to about 20 days (depending on orbital decay parameters). After reactivation a three-day mission and subsequent recovery of the second capsule will complete the active life of the vehicle.

The CORONA-J is dependent on the thrust-assisted Thor-Agena configuration. However, in the event this booster is not immediately successful. a standard CORONA-M system can be flown in the same configuration as currently exists.

As of Il December 1962, I issued termination instructions for the 722 system. This system was designed to obtain area coverage at eight to ten feet resolution with a 36" focal length panoramic steres system. This action was predicated on recovery vehicle problems, and I am now considering the possibility of an experiment using a Thor-Agena vehicle and the proven recovery capsule system to obtain data on the performance of the psyload and the increase in intelligence content inherent in the better resolution system.

Kandie via BrEMAN **Control System** Handle Via TALENT-KEYHOLE Channels Only

TOP SECRET Page L of Pages.

Control No. ST 15384-12 KH plus BY E

TOP SECRET

NRO APPROVED FOR RELEASE
DECLASSIFIED BY: C/IART
DECLASSIFIED ON: 9 JULY 2012

The LANYARD system is a 66" focal length paneramic system with optional stereo capability designed for reconnaissance of specific targets. This system is scheduled for first flight in February 1963. It is completely dependent on success of the thrust-assisted Thoragena vehicle. Recent dynamic resolution tests have obtained 80 to 85 lines/mm at low contrast which is equivalent to about five feet resolution which is the design goal.

The GAMBIT system is the only Atlan-Agens boosted system in the current program. The objective of this 77" focal length strip camera, which also has optional stereo coverage, is to obtain specific target coverage at 2-3 feet resolution. It is acheduled for first flight in June 1963. Dynamic resolution tests of the engineering model of the camera have shown life lines/mm which is above the specification requirement. The major development problems are associated with the control and gtabilization of the vehicle. The desired repolation can be obtained only if vehicle motions are held to maximum values less than those currently obtained in other programs. A major portion of the selution to this problem is dependent on the establishment of an accurate vertical reference by means of horizon sensors and an inertial reference system. There are parallel competitive developments of the horizon sensor, which is the most critical element, and both sensors are new proceeding satisfactorily. The other problem is the accuracy required for pointing the camera at the target. The swath width at madir is only 10.6 nautical miles and exact knowledge of target and vehicle location and precise controllability are necessary. I am considering a proposal to leave the satellite vehicle attached to the Agena during portions of early flights in order to check out exitical elements of the system without complete dependence on proper eperation of the new centrol system.

The ARGON geodetic and mapping system has had two successful tests. Further flights of this system are deferred until next year. I am new considering a proposal for a new geodetic and mapping system with greater capabilities.

Project 617 is a small weather satellite in support of the satellite photographic reconnaissance program. The first successful launch was accomplished 23 August 1962. As of 5 December, 5600 pictures had been received of which 70% were usable. This satellite will probably continue to provide useful information through mid-Jamuary 1963. The next vehicle is ready for launch when the psylend new in orbit ceases to function.

Handle via BYLMAN

Control System

Handle Via TALENT-KEYHOLE

Channels Only


Copy 5 of 7 Copies
Page 2 of 5 Pages.

TOP SECRET Control No. 57 15384-62KH plan BFE


P SECRET

NRO APPROVED FOR RELEA DECLASSIFIED BY: C/IART


DECLASSIFIED ON: 9 JULY 2012



The POPPY type payloads are real time signal repeaters in 20" diameter solar-powered spheres having a long life on erbit. Two POPPY payloads were orbited on 12 December but will not be emercised for several days.



There has been a major effort made to provide the maximum flexibility within the physical constraints of the overall system, and an important aspect of this effort has been to require an interchange—shility of psyloads that could be used on the Thor boosted systems. Currently there exists the possibility at R-35 days to interchange the CORONA, ARGON, LANYARD and CORONA-J psyload subsystems. It is planned that there will be "on the shelf" psyloads svallable so that the launch rate can be increased over the planned schedule in any particular month. It is also possible to replace the entire Agena and



In August of 1963 and every other month thereafter we have programmed a CORONA-J vehicle to be available which will not necessarily be flown in these months. The purpose is to provide a relatively quick-reaction capability which will allow reconnaissance flights to be executed rapidly in future emergency situations. Our launch pads will, however, restrain as from maintaining a sustained rate of more than three Thor-Agenas per month.

Handle via BYEMAN Control System

Handle Via TALENT-KEYHOLE Channels Only Copy 5 of 7 Copies

Page 3 of 5 Pages:

Control No.57 15384-62 KH plus BYE

TOP SECRET

NRO APPROVED FOR RELEASE DECLASSIFIED BY: C/IART DECLASSIFIED ON: 9 JULY 2012

> We are conducting poveral research efforts looking toward extension of our capabilities in the fature. Under the code word VALLEY we have recently initiated a program for design and test of the critical components of a camera system which would provide the severity of the pointing problem inherent with long focal length

GAMBIT or better regolution in a penorumic camera, thus reducing strip type cameras. Project QUILL is research toward an experimental radar payload for bomb damage assessment. In addition to these two payload efforts we have a research study effort with the Martin-Marietta Company to develop hasic design information for a manouversh is lifting re-entry vehicle to permit accurate had recovery of large payloads. I am also evaluating a proposal for a 150" focal length mon-stores strip type system, launched by a thrust-assisted Ther-Agena, which could provide an alternate approach to the resolution we are seeking in the GAMBIT project.

Signed

Atch achedule

Joseph V. Charyk Director National Reconnaignance Office

m: Mr. McNamara Mr. Gilpetric

landle via BYEMAN **'ontrol System**

Handle Via TALENT-KEYHOLE Channels Only

ST.

Jontrol System

NRO APPROVED FOR RELEASE DECLASSIFIED BY: C/IART DECLASSIFIED ON: 9 JULY 2012

HOTOCRAPHIC				F	· M		М	19 J	-	A	s	Q	N	תו	٠.	F	М	A	M		961 .1		S	0	N	D	J	म	M	A	196 .ī
CORONA "M"	10-15° resolution general search		1	Γ	Γ	ī									Ť	Ī					Ť	<u> </u>	Ĭ	Ť		Ĭ					
11,711	10-15' resolution general search						ı	1	1	2	1	2	1	2	ı	2	1	2	1	2	1	2	1	2							
пГп	5* resolution specific coverage			1	1	1	1	ı	1		1	1																			
ARGON	Geodetic coverage 350' resolution					1		ı																							
206 GAMBIT	High resolution 2-3 specific coverage	•						ı		1	1	1	1	1		1	1		ı	1	1	1	ı	ı							

ELECTRONIC

E COTOGRAPHIC

	D	J	F	M.	A I	МJ	J	Α	S	0	N	D	J	F	M	A	M	J	J	A	S	0	N I	D	J]	F	M.	A M	J	J
	£*		****																							de c				
The second secon														-																
					•																						100			
the second secon																										1	1		T -	-
POPPY Long-life real time signal repeaters						ŀ	1															İ								
signal repeaters	1				1		1_	11	1	_						L	1_	L_						\perp						

WEATHER

	D	J F	M A	M J	JA	. S	ON	D.	JF	M A	MJ	J	ASO	N	DJ	F	M A	M_	JJ
417 Weather co (P-35) area of in		1	1		1		1		1]									

C-TETOL NO. ST. 15384 IL HH plus BY E __Copies