

SECURITY CLASSIFICATION **TOP SECRET**

JOINT MESSAGEFORM

SPACE BELOW RESERVED FOR COMMUNICATION CENTER

840 Case Files

(1-2)

L V

PRECEDENCE	TYPE MSG (OMMS)			ACCOUNTING SYMBOL	ORIG. OR REFERS TO	CLASSIFICATION OF REFERENCE
	BOOK	MULTI	SINGLE			

ACTION INFO FROM: 6595 AEROSPACE TEST WG VANDENBERG AFB, CALIF.

TO: SPACE SYSTEMS DIV LOSA CALIF
YWZD - 5211-300

SUBJECT: 8 HOUR FLASH REPORT

I. A VEHICLE CONSISTING OF SLV-2 BOOSTER NO. 356 AND S-01 ORBITAL STAGE NO. 1136 WAS LAUNCHED ON THE FIRST ATTEMPT FROM VAFB COMPLEX 75-3 PAD 4 AT 1404:32.08 PST ON 5 NOVEMBER 1962. THE PRIMARY LAUNCH OBJECTIVE, TO PLACE THE S-01 SATELLITE WITH PAYLOAD IN A NEAR-POLAR ORBIT, WAS ACCOMPLISHED. THE VTS RADAR PLOTBOARD INDICATED THE FOLLOWING APPROXIMATE INJECTION CONDITIONS: ALTITUDE: 130 STATUTE MILES; PAD REFERENCED VELOCITY, 25350 FPS; ELEVATION FLIGHT PATH ANGLE, APPROXIMATELY 0 DEG; AZIMUTH FLIGHT PATH ANGLE, APPROXIMATELY 165 DEG. THE ORBITAL PERIOD ATTAINED APPEARS TO BE NEAR-NOMINAL, BASED ON THE FIRST PASS ACQUISITION.

SPECIAL INSTRUCTIONS

By Authority of _____

Date: 1 APR 1966

CLASSIFICATION CHANGED TO

DATE _____ TIME _____

MONTH _____ YEAR _____

DOWNGRADED AT 3 YEAR INTERVAL
DECLASSIFIED AFTER 12 YEARS
DDO DIRECTIVE 5200.10

WRITER	TYPED NAME AND TITLE (Signature, if required)		SIGNATURE	
	C. S. WALLER, LT. COL. USAF		TYPED (or stamped) NAME AND TITLE	
	PHONE 866-5831	PAGE NR.	NR. OF PAGES	
	SECURITY CLASSIFICATION			

JOINT MESSAGEFORM - CONTINUATION SHEET

SECURITY CLASSIFICATION

FROM

6595 AEROSPACE TEST WG VANDENBERG AFB, CALIF.

PRELIMINARY VALUES OF SIGNIFICANT LAUNCH EVENTS ARE:

LIFTOFF (140432.00 PST)	ZERO
STEERING INITIATED	92.06 SEC
MECO	145.90 SEC (PROPELLANT DEPLETION)
VECO	154.85 SEC
ENABLE D1 AND D2 (S2)	151.04 SEC
D1 ON	153.76 SEC
D1 OFF	156.56 SEC
D2 ON	156.89 SEC
D2 OFF	160.41 SEC
SEPARATION COMMAND (S3)	161.20 SEC
SEPARATION COMPLETE	163.7 SEC
ULLAGE ROCKET IGNITION	179.04 SEC
S-01 ENGINE IGNITION	191.07 SEC
S-01 THRUST ATTAINMENT (90 PER CENT FC)	192.33 SEC
S-01 BURNOUT (70 PER CENT FC)	439.42 SEC
S-01 LINK 2 TELEMETRY FADE	N/A
VTS VERLORT RADAR FADE	455 SEC
VTS ACQUISITION BEACON FADE	481 SEC
VTS TELEMETRY DATA FADE (LINK 1)	487 SEC

PAGE NR

NR OF PAGES

SECURITY CLASSIFICATION

INITIALS

001

2-1

JOINT MESSAGEFORM - CONTINUATION SHEET

SECURITY CLASSIFICATION

[Handwritten signature]
[REDACTED]

FROM

6595 AEROSPACE TEST WG VANDENBERG AFB, CALIF. **[REDACTED]**

II. ALL BOOSTER SUBSYSTEMS PERFORMED SATISFACTORILY AND, IN RESPONSE TO GROUND GUIDANCE SYSTEM COMMANDS, PROVIDED ACCEPTABLE COAST APOGEE CONDITIONS.

MAIN ENGINE SHUTDOWN OCCURRED FROM PROPELLANT DEPLETION RESULTING IN A SLIGHT DEFICIENCY IN COAST APOGEE VELOCITY AS DEFINED BELOW. THIS SMALL ERROR IS WELL WITHIN THE EXPECTED RANGE OF SYSTEM TOLERANCES.

GROUND GUIDANCE SYSTEM DATA INDICATED THAT BOOSTER COAST APOGEE ALTITUDE WAS 106.43 NM (NOMINAL 106.55 NM) AND THE VELOCITY WAS 10,025 FPS (NOMINAL: 10,042 FPS).

III. ALL S-01 VEHICLE SUBSYSTEMS PERFORMED SATISFACTORILY DURING LAUNCH TO PROVIDE THE PROPER TRAJECTORY CONDITIONS AT ENGINE SHUTDOWN.

AT THE TIME OF SIGNAL FADE AT VTS, ALL VEHICLE SUBSYSTEMS WERE FUNCTIONING NORMALLY AND THE ORBITAL TIMER WAS SET AT 5439 SEC (STEP 19), IN THE RESET POSITION, IN THE INCREASE MODE, AND ALTERNATE RE-ENTRY DEARM STATE.

IV. AEROSPACE GROUND EQUIPMENT (AGE)

AEROSPACE GROUND EQUIPMENT FUNCTIONED SATISFACTORILY TO SUPPORT CHECKOUT AND LAUNCH OF THE

SYMBOL	PAGE NO.	NR. OF PAGES	SECURITY CLASSIFICATION	INITIALS
	3		[REDACTED]	

DD FORM 173-1
MAY 66

JOINT MESSAGEFORM - CONTINUATION SHEET

SECURITY CLASSIFICATION

FROM

6495 AEROSPACE TEST WG VANDENBERG AFB, CALIF.

VEHICLE. WITH THE EXCEPTION OF A SLOWER THAN NORMAL RETRACTION OF THE DAC TRANSPORTER - ERECTOR. NO AGE PROBLEMS WERE ENCOUNTERED.

V. COUNTDOWN

VEHICLE 354/1126 WAS LAUNCHED ON THE FIRST ATTEMPT FROM COMPLEX 75-1, PAD 4. THE COUNTDOWN WAS INITIATED ON SCHEDULE AT 0630 PST AND PROCEEDED WITHOUT INCIDENT THROUGH THE TASK COUNTDOWN. TWO HOLDS TOTALLING 4 MIN WERE IMPOSED DURING THE TERMINAL COUNTDOWN.

HOLD NO. 1 WAS IMPOSED IN PHASE V AT 1357 FOR 2 MIN BECAUSE THE TRANSPORTER - ERECTOR WAS RETRACTING SLOWER THAN NORMAL. THE COUNTDOWN WAS RECYCLED TO 95 PER CENT LOX STATUS.

HOLD NO. 2 WAS IMPOSED IN PHASE V AT 1360 FOR 2 MIN TO ALLOW ADDITIONAL TIME FOR THE TRANSPORTER-ERECTOR TO REACH "RETRACT" POSITION. THE COUNTDOWN WAS RECYCLED TO 95 PER CENT LOX STATUS AND PROCEEDED TO NORMAL LIFTOFF.

VI. PAD DAMAGE

THERE WAS A ^{SMALL} FIRE IN THE MAST NEAR THE LAUNCHER DEFLECTOR PLATE CAUSING DAMAGE TO ELECTRICAL INSULATION IN THAT AREA. ALSO THE SECTIONS OF LMSG

SYMBOL

PAGE NR

NR OF PAGES

SECURITY CLASSIFICATION

INITIALS

DD FORM 173-1 MAY 55

JOINT MESSAGEFORM - CONTINUATION SHEET

SECURITY CLASSIFICATION

FROM:

6595 AEROSPACE TEST WG VANDENBERG AFB, CALIF.

AIR CONDITIONING DUCTS AT THE BASE OF THE MAST WERE DESTROYED BY ENGINE BLAST. PAD DAMAGE IS NOT CONSIDERED EXCESSIVE AND RECOVERY CAN BE EFFECTED WITHIN THE SCHEDULED TIME.

13 JUN 1988

00000000

SYMBOL	PAGE NO.	NO. OF PAGES	SECURITY CLASSIFICATION	INITIALS
	5			

DD FORM 173-1 MAY 65